

SPECIFICATIONS FUELTEC MODEL CF75.0AM

Item	SPECIFICATIONS	Model CF75AM	SKU Part Number
1	Chassis powder coated steel	Standard	
2	Air diaphragm Fuel Pump flow rate*	0– 4,500 GPH	
3	Compressed air required for max. flow	60 CFM at 60 PSI	
4	Maximum Lift wet	20 feet	
5	Bag Filters in Stainless Steel Housings six (6) ea.	24 inch bag	241007
6	Fuel Pressure Working Max.	60 PSI	
7	Supply & Return Fuel Hose with cam-lock connectors	2 in. x 25 ft. each	
8	Filter Condition Vacuum Gauges	Two each	
9	Emergency stop air valve	Standard	
10	Casters 4"	Standard	
11	Wheels Flat Free 13"	Standard	
12	Stainless Steel Water Separator Housing	Standard	
13	Supply & Return Ball Valves	Standard	
14	Quick Change Swing Bolt Housing Covers	Standard	
15	Coalescer Elements five (5) ea.	Standard	241024
16	Water Separator Elements two (2) ea.	Standard	241037
17	FILTER MODULE Width X Length X Height.. Lbs.	30x36x52..282 Lbs.	
18	Water Separator Module Width x Length x Height.. Lbs	30x36x59.. 223 Lbs.	