

SPECIFICATIONS

2020 Fueltec Service Trailer W/ Model CF75AM System

| SPECIFICATIONS– CF75AM Fuel Polishing System | Model CF75AM |
|-------------------------------------------------------------------|------------------------|
| Chassis powder coated steel | Standard |
| Air diaphragm Fuel Pump flow rate* | 0– 4,500 GPH |
| Compressed air required for max. flow | 60 CFM at 60 PSI |
| Maximum Lift wet | 20 feet |
| Bag Filters in Stainless Steel Housings six (6) ea. | 24 inch bag |
| Fuel Pressure Working Max. | 60 PSI |
| Supply & Return Fuel Hose with cam-lock connectors | 2 in. x 25 ft. each |
| Filter Condition Vacuum Gauges | Two each |
| Emergency stop air valve | Standard |
| Stainless Steel Water Separator Housing | Standard |
| Supply & Return Ball Valves | Standard |
| Quick Change Swing Bolt Housing Covers | Standard |
| Coalescer Elements five (5) ea. | Standard |
| Water Separator Elements two (2) ea. | Standard |
| FILTER MODULE Width X Length X Height.. Lbs. | 30x36x52..282 Lbs. |
| Water Separator Module Width x Length x Height.. Lbs | 30x36x59.. 223 Lbs. |
| SPECIFICATIONS– Aluminum Trailer 6' X 10' | 6X10 ALUM. TRLR |
| Overall Length 177" X Width 102" Deck 72" X 120" | |
| GVWR 2990 LBS. Tires 205/75R15 Hitch Ball 2" | |
| SPECIFICATIONS- BOSS BULLET AIR COMPRESSOR | |
| Boss oil-flooded, rotary screw air-end up to 70 CFM @ 100 PSIG | |
| 5 Gallon E.P.A / C.A.R.B. approved fuel tank. | |
| Kohler CH-730 25 Hp, 4-cycle, v-twin, air-cooled gasoline engine. | |
| Dimensions: 45"L x 20"W x 30"H 650 lbs. | |
| | |